(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 January 2004 (29.01.2004)

PCT

(10) International Publication Number WO 2004/009292 A1

(51) International Patent Classification7: 5/00, 7/00

B24C 3/00.

(21) International Application Number:

PCT/RU2003/000358

(22) International Filing Date: 23 July 2003 (23.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002119454

23 July 2002 (23.07.2002) RU

2002119455

23 July 2002 (23.07.2002)

(71) Applicant and

(72) Inventor: GRECHISHKIN, Oleg Ivanovich [RU/RU]; ZIISK, der. Sofyino, 18, Naro-Fominsky raion. Moskovskaya obl., 143395 (RU).

(74) Agent: ZEMLYANITSIN, Mikhail Aleksandrovich; Nits "Eldis" Ran, Starosadsky per., 8-1a, Moscow, 101000 (RU).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, II., IN, IS, JP, KE, KG, KP, KR, KZ, I.C, LK, LR, LS, LT, LU, LV. MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GII, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, FT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: ABRASIVE BLASTING DEVICE



(57) Abstract: The device provides for both "cold" and "hot" processing. It comprises a nozzle gun, an abrasive vessel, a batcher, an ejection-type mixer, a fuel tank, a receiver. The nozzle gun comprises a combustion chamber (108), a tubular element (114) for air/abrasive mixture feeding, a nozzle (128), swirlers of the fuel blend (122) and of gaseous oxidant (124). The combustion chamber (108) at its perforated wall area (110) is embodied with variable cross-section. The batcher comprises a means for independent regulation of the seat position with respect to the position of the slide-valve rod, a means for abrasive loosening and blow purging.